



Applicable Radios: PD71XEx/PD79XEx

## Intrinsically Safe Li-ion Battery(1800mAh) BL1807-Ex

The BL1807-Ex Li-ion battery is designed to compliy with ib  $\Pi$ C Ex standards and combine performance ,reliability and various features including the following

- FM, ATEX, IECEx and CSA, standards
- Short-circuit protection
- Overcharge and over discharger protection
- More than 400 cycle times
- IP67 rating

## **SPECIFICATIONS**

Nominal Capacity	1800 mAh
Nominal Voltage	7.4 V
Battery Life (5/5/90 Duty Cycle)	> 10.5 hours (analog) > 14 hours (digital)
	(Varies with frequency settings and radio models)
Dimensions (H x W x D)	120.5 mm x 58 mm x 20.6 mm
Weight	About 174 g
Operating Temperature	0°C to 45°C (charge) −20°C to 60°C (discharge)
Storage Temperature	<ul><li>-20°C to 60°C (one month)</li><li>-20°C to 45°C (three months)</li><li>-20°C to 25°C (one year)</li></ul>
Cycle Life	400 cycles
IP Rating	IP67
Explosion-proof	FM, ATEX, IECEx, CSA, and CQST

<sup>\*</sup>All specifications are tested according to applicable standards, and subject to change without notice due to continuous technological development.

